



# Fast Ethernet Rackmount Switch

## 48 Port

Part No.: 522618

EAN-13: 0766623522618 | UPC: 766623522618

The 48-Port Rackmount Fast Ethernet Switch is a high-performance 10/100 Mbps LAN switch with auto-sensing and auto-negotiation on every port. The space-saving, cost-effective design allows you to connect up to 48 devices to your local area network while only taking up one slot in your network rack or cabinet.

### Auto-Sensing

The 48-Port Rackmount Ethernet Switch automatically senses the speed of the attached device, and self-configures the port to connect at 10 Mbps or 100 Mbps.

### Auto-Negotiation

The 48-Port Rackmount Ethernet Switch will automatically operate at half of full duplex based on the attached device and application being supported.

### Auto-MDI/MDIX Crossover

Each port on the Rackmount Fast Ethernet Switch supports MDI/MDIX, eliminating the need for crossover cables or uplink ports.

### Cost Effective

By supporting up to 48 ports in a single chassis, the 48-Port Fast Ethernet Rackmount Switch saves you money by eliminating the need to purchase an additional switch in order to connect more devices to your growing network.

## Features:

- 10/100 auto-sensing ports automatically detect optimal network speeds
- Supports any combination of 10 Mbps or 100 Mbps network devices
- All RJ45 ports with Auto-MDIX (auto uplink) support
- Auto-detection of full/half duplex modes in all ports
- Supports 802.3x flow control for full duplex mode and collision-based backpressure for half duplex mode
- Supports NWay auto-negotiation
- Non-blocking & non-head-of-line blocking full wire speed forwarding
- Store and forward switching architecture
- Supports up to 8192 MAC address entries
- 512 kBytes buffer memory
- 19" compact rigid metal case
- Includes 19" rackmount brackets
- Three-Year Warranty

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

## Specifications:

### Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (Flow Control and Backpressure)

### General

- Media support:
  - 10Base-T Cat3, 4, 5 UTP/STP RJ45
  - 100Base-TX Cat5 UTP/STP RJ45
- Ports: 48 10/100Base-TX RJ45 ports
- Packet filter/forwarding rate:
  - 148,800 pps (100 Mbps)
  - 14,880 pps (10 Mbps)
- Backplane speed: 9.6 Gbps
- MAC address table: 8192 entries
- Buffer size: 512 kBytes
- Switch architecture: store and forward switch technology
- FCC Class B, CE, RoHS

### LEDs

- Power
- LINK/ACT

### Power input

- Internal power supply: 100 – 240 V AC, 50/60 Hz
- 35 W power consumption
- UL safety approved

### Environmental

- Metal housing, 19" rackmount, 1 U
- Dimensions: 440 (W) x 295 (L) x 44 (H) mm (17.25 x 11.61 x 1.75 in.)
- Weight: 3.0 kg (6.6 lbs.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -40 – 70°C (-40 – 158°F)

### Package contents

- 48-Port Fast Ethernet Rackmount Switch
- Rackmount kit for rack installation
- Power cord
- User manual

