

1080p Passive DisplayPort to HDMI Adapter

DisplayPort Male to HDMI Female, Cable Adapter, 1080p@60Hz, Black

SKU: 151634 | EAN-13: 0766623151634 | UPC: 766623151634

Easily connect a DisplayPort source to an HDMI display

The Manhattan Passive DisplayPort to HDMI Adapter establishes a fast, simple and convenient link between newer DisplayPort-equipped sources and existing HDMI displays. This passive adapter requires DP++ (dual-mode) video/graphics cards to regenerate the signal and ensure the best connection to an HD display. The adapter is easy and quick to install and requires no complicated configuration or setup. The Manhattan Passive DisplayPort to HDMI Cable Adapter is sure to help users fully realize the investment, value and service life of HDMI displays. It offers a passive, compact and integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces orderly.

Features:

- Converts a DisplayPort signal to an HDMI signal
- Supports Deep Color, high-bandwidth 10.8 Gbps applications and HD resolutions at 1080p@60Hz (1920x1200)
- Delivers a high-quality digital video signal — perfect for connecting a new DisplayPort source to an existing HDMI display
- Passive adapter requires DP++ (dual-mode) video/graphics cards to regenerate the signal and ensure the best connection to an HD monitor, projector and more
- Integrated design simplifies and eliminates cable tangles; latching connector ensures secure connection
- Easy installation; Plug and Play
- Three-year warranty

Specifications:

Standards and Certifications
• UL 20276
• DisplayPort v1.1
• FCC
• CE
• HDCP

General
• 8-bit and 10-bit Deep Color support
• 10.8 Gbps bandwidth
• Maximum single link resolution: 1920x1200 (1080p@60Hz)
• Auxiliary channel support: 1 Mbps
• One-lane, one-direction, four-line connection support
• Passive

Connections
• DisplayPort 20-pin male (latching)
• HDMI 19-pin female
• Gold-plated contacts
• Molded PVC

Physical
• Dimensions: 20 x 2.2 x 1.4 cm (5.91 x 0.87 x 0.55 in.)
• Cable length: 15 cm (5.91 in.)
• Weight: 14 g (0.5 oz.)

Operating Environment

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• Operation Temperature: 0 – 40°C (32 – 104°F)
• Storage Temperature: -20 – 60°C (-4 – 140°F)
• Humidity (noncondensing): 0 – 96%

System Requirements
• Windows XP/Vista/7/8/8.1/10, Linux or Mac 9.x/10.x or above

Package Contents
• Passive DisplayPort to HDMI Adapter









All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.



For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.