

High Speed HDMI Cable with Ethernet

4K@30Hz UHD, HDMI Male to Male, 1.8 m (6 ft.), HEC, ARC, Double Shielded, Black

SKU: 355728 | EAN-13: 0766623355728 | UPC: 766623355728

4K HDMI Cable - Ultra-High-Definition (UHD) performance up to 4K@30Hz

HDMI is the gold standard for delivering the highest-quality audio and video signals over a single cable from an AV source to your display or projector. Use this Manhattan High Speed HDMI Cable with every HDMI device - TVs, projectors, monitors, notebooks, PCs, AV receivers, streaming boxes, game consoles, PlayStation® (PS4/PS5), Xbox® (One/One X/Series S/Series X), Blu-ray players and more. It is designed and carefully constructed to meet the evolving needs of the 4K UHD marketplace. Expanded features include an Audio Return Channel to allow your TV's audio to transmit through your audio system without a separate cable. It includes Internet connectivity for home entertainment devices thanks to the integrated HDMI Ethernet Channel (HEC). Double shielding (aluminum foil and Mylar braid) helps prevent EMI issues to keep your video output crystal clear.

Features:

- Supports Ultra-High-Definition (UHD) 4K@30Hz; up to 1080p resolution in 3D and Deep Color
- Compliant with High Speed HDMI specifications
- Foil and braid double shielding to reduce EMI and other interference sources
- Audio Return Channel (ARC) to allow TV's audio to transmit through your audio system without a separate audio cable
- HDMI Consumer Electronics Control (CEC) so one remote can be used with all compatible HDMI devices
- HDMI Ethernet Channel (HEC) to add network connectivity to an HDMI link without a separate Ethernet cable
- Compatible with every HDMI device - TVs, projectors, monitors, notebooks, PCs, AV receivers, streaming boxes, game consoles, PlayStation® (PS4/PS5), Xbox® (One/Series S/Series X), Blu-ray players and more
- Molded PVC boot
- HDCP 2.2 compliant
- Lifetime warranty

Specifications:

Standards and Certifications
• CE
• RoHS

General
• 4K (3840 × 2160) at 30 Hz resolution
• HDCP 2.2 support
• CEC support
• HDR support
• ARC support

Connectors
• Two HDMI 19-pin male
• Nickel-plated contacts

Cable
• 30 AWG
• Double shielding: aluminum foil and Mylar braid
• Current rating: 0.5 A DC
• Withstanding voltage: 300 VDC
• Insulation resistance: 5 MOhm
• Contact resistance: 2 Ohm
• PVC jacket
• Length: 1.8 m (6 ft.)
• Other dimensions: 20 mm ± 0.2 mm (width), 11 ± 0.2 mm (height)

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• Weight: 85 g (3 oz.)

Package Contents
• High Speed HDMI Cable







All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.